

Video Security



VK-134

1/3" B/W Board Camera in Housing
with 3.6mm Lens, 12VDC, 380TVL

Art-No. 91747



Features

CCD B&W Board Camera with Housing
1/3" CCD Sensor
Resolution of 380 Horizontal Lines
Electronic Shutter Control (ESC)
Internal Synchronization

High Sensitivity
Interchangeable Lens Element
Supply Voltage: 12 VDC
Micro Compact Version

Specifications

System	black/white
Video standard	CCIR
Imager	CCD, Sony Super HAD Interline Transfer CCD
Sensor size	1/3"
Active picture elements	Approx. 290,000 (H) 500 x (V) 582
Synchronization	Internal
Gamma correction	0.45
Sensitivity (at 50% video signal)	0,58Lux, at F1.2 (VT measurement result), 1.6Lux at F2.0
Integration rate	no
Backlight compensation	no
Aperture Correction (APC)	Yes
IR cut filter	no
Mount	n/a
Lens	F2.0/3.6mm
Application range	security
Nominal format size	1/3"
Aspherical technology	no
Focal length	3,6mm
Horizontal angle of view	69°

VK-134

(Specifications continued)

Iris control	no
Lens mount	integrated lens
External connections	Video (BNC), 12 VDC (DC socket)
Video outputs (type)	VBS
Video outputs	1Vp-p, VBS, 750hm
Serial interfaces	no
Supply voltage	12VDC, 12 VDC (+/-10%)
Power consumption	1.2watts
Temperature range (Operation)	-10° ~ +50°C
Dimensions (HxWxD)	32x32x28 mm
Weight	48 g

Accessories

40059 / H0225M	F2.5/2.5mm Board Camera Lens, 1/3" M12X0.5
40072 / H0620M	F2.0/6mm Board Camera Lens, 1/3" M12x0.5
40061 / H0820M	F2.0/8mm Board Camera Lens, 1/3" M12X0.5
70447 / VT-PS12DC-5	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug

Sicherheitssysteme Uebachs GmbH
Your Contact: Fridtjof Uebachs
Königsallee 22 · 40212 Düsseldorf
Phone 0211-210744-0 · Fax 0211-210744-29
technik@uebachs.de · www.uebachs.de

